



The Acoustic Ones



Special Boosters

Special boosters 35 kHz / 20 kHz

The special boosters are suitable for the amplification of the amplitude in special applications.





- Suitable for special applications of various kinds
- The ideal booster for every application thanks to a great diversity of amplification factors and materials
- Heavy duty
- Low-loss and true to amplitude

Specification special boosters

Operating frequency:	35 kHz / 20 kHz	
Weight:	Booster 35 kHz: 350 g Booster 20 kHz: 1.5 kg	
Housing:	Booster 35 kHz: Nickel-plated steel, booster with thread for height adjustment Booster 20 kHz: Nickel-plated steel, without shoulder	
Amplification factors:	Booster 35 kHz with thread:	Aluminium: 1:1 / 1:1.5
		Titanium: 1:2 / 1:2.5 / 1:3
	Booster 35 kHz with thread elastic:	Aluminium: 1:1.5
		Titanium: 1:2
	Booster 20 kHz without shoulder:	Aluminium: 1:1 / 1:1.5
	Booster 20 kHz with shoulder elastic:	Aluminium: 1:1 / 1:1.5
		Titanium: 1:2

Additional technical information available on request.



RINCO ULTRASONICS AG
 CH-8590 Romanshorn 1
 Tel. +41 71 466 41 00
 Fax +41 71 466 41 01
info@rincoultrasonics.com
www.rincoultrasonics.com