

## HG/HW 35-3

## Ultrasonic hand welding units 35 kHz

The ultrasonic hand welding units HG35-3 and HW35-3 are suitable for manual welding and cutting operations from sma to medium size.





- Ideal for spot welding, riveting, beading or cutting with template horns
- . Operable with RL and SL generators
- . Rugged construction for optimal sound propagation
- Protected cable duct

## Specification HG35-3/HW35-3

Operating frequency:	35 kHz	
Switches:	On the hand grip	
Weight:	HW35-3:	0.7 kg including transducer
	HG35-3:	1.2 kg including converter
		1.5 kg including converter and booster
Horns:	Customized, position of horn can be rotated by 90°	
Amplitude amplification:	HW35-3:	Integrated transducer (amplified 1:1.5)
		Integrated transducer (unamplified)
	HG35-3:	Converter C35-11/13 (amplified 1:1.5), not included
		Converter C35-10/12 (unamplified) with booster 1:2, not included
Cable set:	HW35-3:	3 m standard
	HG35-3:	3 m standard with integrated inner tube
	Special lengths 7 m/11 m/15 m on request	
Generator:	Suitable types: <b>RL35</b> -250/400/600, <b>SL35</b> -400/600	
Options:	HW35-3:	Pressurized air cooling for converter retrofit
	HG35-3:	Pressurized air cooling for converter and horn retrofit

Additional technical information available on request.



## **RINCO ULTRASONICS AG**

CH-8590 Romanshorn 1 Tel. +41 71 466 41 00 Fax +41 71 466 41 01 info@rincoultrasonics.com www.rincoultrasonics.com